



DB844G65ZAXY

Directed Dipole Antenna

Decibel®
Base Station Antennas

- Exceptional azimuth roll-off, reducing sector-to-sector interference and softer hand-offs
- Air dielectric feed system, no screws, rivets, welds or solder in RF element feed path
- Strong upper side lobe suppression
- Low profile appearance and low wind loading for easier zoning approvals

ELECTRICAL

Frequency (MHz) :	806 - 896	870 - 960
Polarization :	Vertical	Vertical
Gain (dBd/dBi) :	13.5/15.6	13.8/15.9
Azimuth BW (Deg.):	65	65
Elevation BW (Deg.):	15	15
Beam Tilt (Deg.):	0	0
USLS* (dB) :	15	15
Null Fill (dB) :	<20-25	<20-25
Front-To-Back Ratio* (dB) :	40	40
VSWR :	<1.33:1	<1.33:1
PIM3 @ 2 x 20w (dBc) :	-150	-150
Max. Input Power (Watts) :	500	500
Impedance (Ohms) :	50	50
Lightning Protection :	DC Ground	DC Ground



MECHANICAL

Weight :	5.4 kg (12 lb)
Dimensions (LxWxD) :	1,219 x 254 x 203 mm (48 x 10 x 8 in)
Max. Wind Area :	0.09 m ² (1 ft ²)
Max. Wind Load (@ 100 mph) :	235.7 N (53 lbf)
Max. Wind Speed :	241 km/h (150 mph)
Hardware Material :	Galvanized Steel
Connector Type :	7-16 DIN - Female (1, Back)
Color :	Light Gray
Standard Mounting Hardware :	DB380
Standard Downtilt Mounting Hardware :	DB5083




DB844G65ZAXY

Directed Dipole Antenna


Decibel®
Base Station Antennas

AZIMUTH PATTERN



Freq: 880 MHz, Tilt: 0

ELEVATION PATTERN



Freq: 880 MHz, Tilt: 0